

Certified PREMIUM SELECTION WOOD PELLET

Ø 6 mm



- ✓ guaranteed product quality
- ✓ low ash
- ✓ high calorific value



www.biomasapartner.pl

Recommended by boiler manufacturers

In harmony with nature

TECHNICAL PARAMETERS

Total moisture content	< 8%
Ash content	< 0.55%
Calorific value	> 17.5 MJ/kg
Bulk density	600 < BD < 750 kg/m ³
Fine fraction content (dust in bag)	< 0.5%
Mechanical strength	> 98.0%
Diameter	6 mm
Length	3.15 < L < 40 mm

PACKAGING

Unit packaging	15 kg bags, 1000 kg big bags
Bulk packaging	90 x 110 cm pallet/100 x 120 cm
Bulk	

STORAGE

It is advisable to store the pellets in dry rooms that are not exposed to extreme weather conditions. The bags should be insulated from the ground by being stored on pallets.

PRODUCT CHARACTERISTICS

Production is carried out using pine sawdust without bark or impurities.

The high calorific value and low ash content enable more heat to be obtained from one tonne of pellets.

Held certification guarantees high quality and repeatability of the product batch.

Boiler manufacturers recommend Premium Selection Pellets as the best fuel, as they allow the user to comply with the terms of the boiler warranty.

MANUFACTURER

Biomasa Partner Group SA
tel. +48 530 921 166
e-mail: pellet@biomasapartner.pl

Distribution:

We guarantee safe transport of your pellets!

